SKAALA
member of IFN



SKAALA BEETA 2020

Skaala Beeta 2020 - more light

The new design in outer aluminium makes this product lighter and enlarges the light opening letting the maximum amount of natural light to indoors.

This window is easy designed to be easy in use. Additional features - astragals and mosquito nets - are easy to use. Aluminium for minimum maintenance and long service life.



Thanks to light outher aluminium sash Skaala Beeta 2020 opens the scenery indoors.

Window type

- Triple-glazed, inward opening timber-aluminum window with aluminum outer casement
- Frame finger jointed engineered timber. The outer casement and outer cladding of frame powder coated aluminum.
- Frame depths 175 mm, 131 mm and 210 mm.

Glazing

- Standard glazing in inner casement double IG-unit with SuperSpacer and argon filling.
- Standard outer casement with anti-condensation float glass in Beeta0,8.

Surface treatment and size limits

- Wood: standard colour white NCS 0502-Y.
- ALuminium, standard colours: white RAL9010, grey RAL7024, brown RR32, grey RAL7040 and black RAL 9005.
- See other possibilities in RAL-map.

- minimum heigth/ width 270 mm
- maximum heigth/ width 2690 mm
- max. surface of an opening sash 4 m^2.

Options

- Venetian blinds, traditional or integrated.
- Mosquitonet to ventilation window
- Ventilation solutions
- Astragals
- Various glazing options: frostfree, safety, signal, sound reducing or solar protection.

Performance (frame depth 175 mm):

U-value	Thermal transmittance	0,8 - 1,0 W/m^2K
G-value	Solar transmittance	0,36 gw
dB	Sound reduction	46(-1;-4) Rw